

TYRES

Product group	Tyres
Item number	72400265
Valid tyre size	650 / 75 R 32 CHO
LI / SI / PR	172 A8 / 172 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Teris
Sonderpostenkategorie	Damaged
type of damage	Stud damage



Notes and features

- Super-volume tyre for harvesters, self-propelled machinery for spreading nutrients and other agricultural vehicles.
- Offers high load capacities, even at low inflation pressures and in cyclical use.
- Very large contact area for optimum ground pressure distribution and outstanding traction.
- Sidewall protectors protect against damage.
- High number of polyester belt plies for improved handling and stability in use.

Technical Informations

Item number	72400265
Valid tyre size	650 / 75 R 32 CHO
LI / SI / PR	172 A8 / 172 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Teris
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	261,80
Recommended rim size	21
Permitted rim size	20, 23
Maximum air pressure [bar].	3,20
Section width (mm)	670
Outer diameter of tyre [mm].	1795
Stat. radius (SLR) [mm]	816
Rolling circumference [mm].	5378
Tread depth (mm)	60,0
Number of lugs	22x2
Tyre capacity 75% [ltr.]	642
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
172 A8	6300	40		3,20	
172 B	6300	50		3,20	