Bohnenkamp Moving Professionals

TYRES

Product group	Tyres	
Item number	72400266	
Valid tyre size	IF 650 / 85 R 38 CFO	
LI / SI / PR	179 D	
TL/TT	TL	
Brand	ВКТ	
Tread pattern	Agrimax Force	
Sonderpostenkategorie	Disassambled	
type of damage	Dismounted,Cut in the flank	



Notes and features

- BKT Agrimax Force is an IF tyre for high performance • tractors with more than 250 hp.
- It offers 20% higher load capacity at the same air • pressure or the same load capacity at 20% lower air pressure compared to a standard tyre.
- The large contact area enables a uniform distribution of . ground pressure and therefore optimum soil protection.
- Its strong polyester belt carcass provides good traction . and stability on all surfaces and long tyre life.
- The tyre guarantees driving comfort in the field and during • transport trips on the road without the need to adjust the air pressure.

Bohnenkamp Moving Professionals

Technical Informations

Item number	72400266
Valid tyre size	IF 650 / 85 R 38 CFO
LI / SI / PR	179 D
TL/TT	TL
Brand	ВКТ
Tread pattern	Agrimax Force
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	362,20
Recommended rim size	DW23B
Permitted rim size	DW20B, DW21B
Maximum air pressure [bar].	2,40
Section width (mm)	663
Outer diameter of tyre [mm].	2071
Stat. radius (SLR) [mm]	927
Speed Radius Index (SRI)	975
Rolling circumference [mm].	6106
Tread depth (mm)	64,5
Number of lugs	23x2
Tyre capacity 75% [ltr.]	838.1
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
179 D	7750	65		2,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.