

TYRES

Product group	Tyres
Item number	72400272
Valid tyre size	425 / 65 R 22.5
LI / SI / PR	165 K, 20 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WTR 69
Sonderpostenkategorie	Disassembled
type of damage	Dismounted,Irregular run



WINDPOWER
Get Your Job Done

Notes and features

- Modern, multifunctional trailer tyre for local, regional and long-distance transport.
- Long-life compound, flexible tread pattern for a long service life.
- Reinforced, wide tyre shoulder.

Technical Informations

Item number	72400272
Valid tyre size	425 / 65 R 22.5
LI / SI / PR	165 K, 20 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WTR 69
M+S	M+S
3PMSF	3PMSF
Axle position truck	TR
Rolling resistance	C
Wet grip	D
Rolling noise [db].	71
Rolling noise level	A
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	88,30
Recommended rim size	13.00
Permitted rim size	14.00
Maximum air pressure [bar].	8,30
Section width (mm)	421
Outer diameter of tyre [mm].	1119
Stat. radius (SLR) [mm]	518
Speed Radius Index (SRI)	525
Rolling circumference [mm].	3413
Tread depth (mm)	16,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
165 K	5150	110	Single	8,30	