

TYRES

Product group	Tyres
Item number	72400273
Valid tyre size	15.0 / 55 - 17
LI / SI / PR	128 A8 / 141 A8, 14 PR
TL/TT	TL
Brand	BKT
Tread pattern	AS 504
Sonderpostenkategorie	Disassembled
type of damage	Dismounted,Irregular run



Notes and features

- The BKT AS 504 is a versatile agro-industrial tyre for transport and soil cultivation
- It is characterised by excellent self-cleaning properties and increased adhesion, ideally suited for use on muddy ground
- Some sizes were developed for loading work and for use in hay harvesting

Technical Informations

Item number	72400273
Valid tyre size	15.0 / 55 - 17
LI / SI / PR	128 A8 / 141 A8, 14 PR
TL/TT	TL
Brand	BKT
Tread pattern	AS 504
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	34,34
Recommended rim size	13.00
Permitted rim size	13
Maximum air pressure [bar].	3,70
Section width (mm)	380
Outer diameter of tyre [mm].	890
Stat. radius (SLR) [mm]	395
Rolling circumference [mm].	2608
Tread depth (mm)	23,0
Number of lugs	17x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
128 A8	1800	40	Drive Wheel	3,70	LLV
141 A8	2575	40	Free Rolling	3,70	LLV