Bohnenkamp Moving Professionals

TYRES

Product group	Tyres
Item number	72400274
Valid tyre size	VF 650 / 65 R 42
LI / SI / PR	174 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agristar 365
Sonderpostenkategorie	Disassambled
type of damage	Dismounted





Notes and features

- Agricultural radial wide tyre of the 65 series (70 series • with 710 width) for powerful tractors up to approx. 250 hp.
- Very gentle tillage due to high air volume and large • contact area.
- Lug shape and arrangement allows optimum traction . power distribution.
- With 65 km/h approval, suitable for frequent road use. •

Bohnenkamp Moving Professionals

Technical Informations

Item number	72400274
Valid tyre size	VF 650 / 65 R 42
LI / SI / PR	174 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agristar 365
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	253,00
Recommended rim size	DW20B
Permitted rim size	DW21B, DW18
Maximum air pressure [bar].	2,00
Section width (mm)	650
Outer diameter of tyre [mm].	1935
Stat. radius (SLR) [mm]	842
Rolling circumference [mm].	5611
Tread depth (mm)	58,0
Number of lugs	22x2
Tyre capacity 75% [ltr.]	684.75
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
174 D	6700	65		2,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.