

TYRES

Product group	Tyres
Item number	72400286
Valid tyre size	340 / 85 R 48
LI / SI / PR	152 A8 / 152 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 955
Sonderpostenkategorie	Disassembled
type of damage	Dismounted



Notes and features

- Row crop tyre for use on tractors as well as self-propelled and towed field sprayers
- Also offers good ride comfort on the road
- Rounded shoulders provide protection against plant and ground damage
- High load capacity also enables use with heavy attachments
- Offers high machine stability and very good ride comfort, approved up to 50 km/h

Technical Informations

Item number	72400286
Valid tyre size	340 / 85 R 48
Alternative size 1	13.6R48
LI / SI / PR	152 A8 / 152 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 955
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	108,41
Recommended rim size	W12
Permitted rim size	W11
Maximum air pressure [bar].	4,00
Section width (mm)	353
Outer diameter of tyre [mm].	1797
Stat. radius (SLR) [mm]	855
Rolling circumference [mm].	5572
Tread depth (mm)	36,5
Number of lugs	29x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
152 A8	3550	40		4,00	
152 B	3550	50		4,00	