

TYRES

Product group	Tyres
Item number	72400289
Valid tyre size	800 / 65 R 32
LI / SI / PR	172 A8 / 172 B
TL/TT	TL
Brand	Alliance
Tread pattern	Agristar 375
Sonderpostenkategorie	Damaged
type of damage	Stud damage



Notes and features

- Super-volume tyre for harvesters, self-propelled machinery for spreading nutrients and other heavy farm machinery.
- Aggressive R-1W tread pattern for maximum traction and low slip.
- Offers enormous load capacities even at low inflation pressures.
- Steel belts and a special stubble guard rubber compound make the tyre even tougher against punctures from corn stubble, for example.

Technical Informations

Item number	72400289
Valid tyre size	800 / 65 R 32
LI / SI / PR	172 A8 / 172 B
TL/TT	TL
Brand	Alliance
Tread pattern	Agristar 375
TRA Code	R1-W
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	340,20
Recommended rim size	DW27A
Maximum air pressure [bar].	2,70
Section width (mm)	812
Outer diameter of tyre [mm].	1845
Stat. radius (SLR) [mm]	845
Rolling circumference [mm].	5529
Guarantee period	10 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
172 A8	6300	40		2,40	
172 B	6300	50		2,40	