## Bohnenkamp Moving Professionals

21.09.2024

### **TYRES**

Product group	Tyres
Item number	72400293
Valid tyre size	710 / 50 R 26.5
LI / SI / PR	172 D
TL/TT	TL
Brand	Alliance
Tread pattern	390
Sonderpostenkategorie	Damaged
type of damage	Stud damage





#### Notes and features

- Ideal for longer transport and grassland use.
- Block tread pattern for smooth handling on long road journeys and soil protection when driving on grassland.
- Low rolling resistance for minimum fuel consumption.
- High tread depth for a long service life.
- Steel belt reinforcement for high load capacities and improved stability.

# Bohnenkamp Moving Professionals

### **Technical Informations**

Item number	72400293
Valid tyre size	710 / 50 R 26.5
LI / SI / PR	172 D
ть/тт	TL
Brand	Alliance
Tread pattern	390
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	184,97
Recommended rim size	24.00
Maximum air pressure [bar].	4,00
Section width (mm)	730
Outer diameter of tyre [mm].	1390
Stat. radius (SLR) [mm]	627
Dynamic radius [mm]	647.1
Speed Radius Index (SRI)	675
Rolling circumference [mm].	4100
Tread depth (mm)	26,0
Lug width (mm)	84-96
Guarantee period	10 years
E-Ready	No

### Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
172 D	6300	65		4,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.