

TYRES

Product group	Tyres
Item number	72400306
Valid tyre size	23.1 - 26
LI / SI / PR	172 A2, 16 PR
TL/TT	TL
Brand	Maxam
Tread pattern	MS931 LOGXTRA
Sonderpostenkategorie	Damaged
type of damage	Flap damage





Notes and features

- The Maxam MS931 LOGXTRA is a bias forestry tyre for skidders, loggers and similar forestry machines.
- Its high-strength, steel-reinforced construction ensures excellent traction.
- The robust tyre shoulder and sidewall as well as the cutresistant rubber compound protect the tyre from damage.
- The particularly large contact area guarantees very good flotation on wet and muddy ground.
- The nylon-wrapped tyre bead prevents the tyre from coming off the rim during forestry work in difficult conditions.



Technical Informations

Item number	72400306
Valid tyre size	23.1 - 26
LI / SI / PR	172 A2, 16 PR
TL/TT	TL
Brand	Maxam
Tread pattern	MS931 LOGXTRA
TRA Code	LS-2
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	280,20
Recommended rim size	DW20B
Maximum air pressure [bar].	2,75
Section width (mm)	580
Outer diameter of tyre [mm].	1620
Stat. radius (SLR) [mm]	747
Speed Radius Index (SRI)	775
Rolling circumference [mm].	4980
Tread depth (mm)	58,0
Number of lugs	15x2
Tyre capacity 75% [ltr.]	442
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
172 A2	6300	10		2,75	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.