

## **TYRES**

Product group	Tyres	
Item number	72400307	
Valid tyre size	710 / 70 R 42	
LI / SI / PR	179 D	
TL/TT	TL	
Brand	Nokian	
Tread pattern	Tractor King	
Sonderpostenkategorie	Disassambled	
type of damage	Runout	



## Notes and features

- The Nokian Tractor King is a tractor tyre for heavy machines on rough terrain, in forestry and earthmoving applications and on building sites.
- Due to the strong steel belted casing and the robust sidewall, the tyre is protected against damages and premature wear.
- Its big contact area and the innovative tread pattern with a high number of traction edges guarantee good traction on any surface.
- Stone ejectors prevent damage caused by the penetration of stones and thus ensure a long service life for the tyre.
- The tyre can be fitted with spikes and driven with tyre chains.
- It provides high loading capacities at speeds up to 65 km/h.



## **Technical Informations**

Item number	72400307
Valid tyre size	710 / 70 R 42
LI / SI / PR	179 D
TL/TT	TL
Brand	Nokian
Tread pattern	Tractor King
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	440,73
Recommended rim size	DW23B
Permitted rim size	TW25B, TW23B
Maximum air pressure [bar].	3,20
Section width (mm)	716
Outer diameter of tyre [mm].	2061
Stat. radius (SLR) [mm]	975
Rolling circumference [mm].	6267
Tread depth (mm)	56,0
Tyre capacity 75% [ltr.]	900
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
179 D	7750	65		3,20	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.