

RIMS

Product group	Rims
Item number	72400313
Valid rim size	11.75 x 22.5 H
Rim connection	10/281/335
Bolt hole design	B33
Rim colour	Silver
Brand	Covex
Sonderpostenkategorie	Disassambled
type of damage	Dismounted,Paint damage



Technical Informations

Load capacity of rim 1 [kg]	5000
Speed Rims 1 [km/h]	130
Maximum speed [km/h].	130
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	41,28
Hump	Н
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	11

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Verschweißung beidseitig	No
Ventilation holes	Yes
Rim centering	внс
Number of bolt holes	10
Bolt hole diameter [mm]	26
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	9.7
Preassembled valve	Yes
TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve designation ETRTO	V3.20.1
Valve length [mm]	41
Valve angle [°]	gerade
Valve cap Material	Steel