

TYRES

Product group	Tyres	
Item number	72400314	
Valid tyre size	385 / 55 R 18	
LI / SI / PR	140 A8 / 140 B	
TL/TT	TL	
Brand	Alliance	
Tread pattern	601	
Sonderpostenkategorie	Disassambled	
type of damage	Paint damage, Dismounted	





Notes and features

- For small wheel loaders and excavators with M+S marking.
- Radial tyre with strong nylon construction and steel belt.
- High contact area ensures good pressure distribution.



Technical Informations

Item number	72400314
Valid tyre size	385 / 55 R 18
Alternative size 1	15.5/55R18
LI / SI / PR	140 A8 / 140 B
TL/TT	TL
Brand	Alliance
Tread pattern	601
M+S	M+S
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	41,38
Recommended rim size	11
Maximum air pressure [bar].	3,50
Section width (mm)	370
Outer diameter of tyre [mm].	890
Stat. radius (SLR) [mm]	395
Rolling circumference [mm].	2686
Tread depth (mm)	17,0
Tyre capacity 75% [ltr.]	133
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
140 A8	2500	40		3,50	
140 B	2500	50		3,50	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.