

TYRES

| Product group | Tyres |
|-----------------------|-------------------|
| Item number | 72400315 |
| Valid tyre size | 385 / 55 R 18 |
| LI / SI / PR | 140 A8 / 140 B |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | 601 |
| Sonderpostenkategorie | Damaged |
| type of damage | Hole in the flank |





Notes and features

- For small wheel loaders and excavators with M+S marking.
- Radial tyre with strong nylon construction and steel belt.
- High contact area ensures good pressure distribution.



Technical Informations

| Item number | 72400315 |
|------------------------------|----------------|
| Valid tyre size | 385 / 55 R 18 |
| Alternative size 1 | 15.5/55R18 |
| LI / SI / PR | 140 A8 / 140 B |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | 601 |
| M+S | M+S |
| Carcass properties | Steel Belted |
| Antistatic | No |
| Tyre colour | Black |
| Nettogewicht [kg] (gültig) | 41,38 |
| Recommended rim size | 11 |
| Maximum air pressure [bar]. | 3,50 |
| Section width (mm) | 370 |
| Outer diameter of tyre [mm]. | 890 |
| Stat. radius (SLR) [mm] | 395 |
| Rolling circumference [mm]. | 2686 |
| Tread depth (mm) | 17,0 |
| Tyre capacity 75% [ltr.] | 133 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|-----------------------------|--------------|
| 140 A8 | 2500 | 40 | | 3,50 | |
| 140 B | 2500 | 50 | | 3,50 | |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.