

TYRES

Product group	Tyres
Item number	72400324
Valid tyre size	540 / 65 R 28
LI / SI / PR	152 A8 / 149 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 657
Sonderpostenkategorie	Damaged
type of damage	Stud damage



Notes and features

- The BKT Agrimax RT 657 is a wide tyre of the 65 series in the power range up to 250 hp.
- Due to the solid lugs and the large contact area, the tyre provides excellent traction even when working on the most difficult soils.
- At the same time, its high air volume and variable inflation pressure adjustment ensure optimum soil protection.
- On the road, the tyre guarantees high ride comfort combined with low rolling resistance and thus low fuel consumption.
- For road transport, the tyre is approved for speeds up to 65 km/h.

Technical Informations

Item number	72400324
Valid tyre size	540 / 65 R 28
LI / SI / PR	152 A8 / 149 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 657
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	126,78
Recommended rim size	W16L
Permitted rim size	W18L, W15L
Maximum air pressure [bar].	2,40
Section width (mm)	530
Tread width (mm)	510
Outer diameter of tyre [mm].	1413
Stat. radius (SLR) [mm]	643
Speed Radius Index (SRI)	675
Rolling circumference [mm].	4253
Tread depth (mm)	50,0
Number of lugs	19x2
Lug width (mm)	39
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
152 A8	3550	40		2,40	
149 D	3250	65		2,40	