

WHEELS

Product group	Wheels
Item number	72400327
Valid wheel size	385 / 65 R 22.5
Brand	Sailun
Tread pattern	STL1
Valid rim size	11.75 x 22.5
Rim connection	10/281/335
Bolt hole design	M22
Offset (mm)	+120
Half centre distance (HMA) [mm]	133.1
Rim colour	Silver
Load capacity complete wheel [kg]	4500
Speed complete wheel [km/h]	110
Sonderpostenkategorie	Remaining stock
type of damage	Rest profile
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



SAILUN
TYRE

Technical Informations

LI / SI / PR	160 K (158 L), 20 PR
Load capacity 1 [kg]	4500
Speed 1 [km/h].	110
Load capacity 2 [kg]	4250
Speed 2 [km/h].	120
M+S	M+S
3PMSF	3PMSF

Axle position truck	TR
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	0,00
ECE regulation number	ECE 54 ECE 117
Section width (mm)	389
Stat. radius (SLR) [mm]	495.96
Rolling circumference [mm].	3103
Tread depth (mm)	13,0
Rolling resistance	B
Wet grip	B
Rolling noise [db].	71
Rolling noise level	A
E-Ready	No
Load capacity of rim 1 [kg]	5000
Speed Rims 1 [km/h]	130
Maximum speed [km/h].	120
Maximum air pressure [bar].	9,00
Number of bolt holes	10
Bolt hole design EUWA	M22
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Bolt hole diameter [mm]	26
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim centering	HB

Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	9.7
Preassembled valve	No
TPMS-kompatibles Ventil	No