

TYRES

| | |
|-----------------------|-----------------|
| Product group | Tyres |
| Item number | 72400332 |
| Valid tyre size | 710 / 50 R 26.5 |
| LI / SI / PR | 170 D |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | Flotmaster 381 |
| Sonderpostenkategorie | Damaged |
| type of damage | Flap damage |



Notes and features

- Steel belted tyre for use on grassland.
- Rounded shoulders for optimum soil and turf protection.
- Non-directional tread pattern.
- Low soil compaction due to large contact area.
- High tread pattern percentage and low rolling resistance for optimum fuel efficiency.
- Ideal for silage trailers and transport vehicles for green fodder harvesting.

Technical Informations

| | |
|------------------------------|-----------------|
| Item number | 72400332 |
| Valid tyre size | 710 / 50 R 26.5 |
| LI / SI / PR | 170 D |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | Flotmaster 381 |
| Carcass properties | Steel Belted |
| Antistatic | No |
| Tyre colour | Black |
| Nettogewicht [kg] (gültig) | 145,20 |
| Recommended rim size | 24.00 |
| Maximum air pressure [bar]. | 4,00 |
| Section width (mm) | 710 |
| Outer diameter of tyre [mm]. | 1360 |
| Stat. radius (SLR) [mm] | 610 |
| Rolling circumference [mm]. | 4171 |
| Tread depth (mm) | 20,0 |
| Tyre capacity 75% [ltr.] | 573 |
| Guarantee period | 10 years |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 170 D | 6000 | 65 | | 4,00 | |