

TYRES

Product group	Tyres
Item number	72400334
Valid tyre size	480 / 70 R 34
LI / SI / PR	149 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 765
Sonderpostenkategorie	Damaged
type of damage	Puncture at tyre shoulder



Notes and features

- Wide-base tyre of the 70 series for tractors in the low to medium-power range.
- Mainly used both in arable farming and grassland.
- Low soil compaction and good self-cleaning properties.
- Optimized rubber compound: 25% less wear, 30% improved cut and release resistance and 20% more traction.

Technical Informations

Item number	72400334
Valid tyre size	480 / 70 R 34
LI / SI / PR	149 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 765
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	128,20
Recommended rim size	W15L
Permitted rim size	W14L, W16L
Maximum air pressure [bar].	2,40
Section width (mm)	479
Outer diameter of tyre [mm].	1580
Stat. radius (SLR) [mm]	711
Rolling circumference [mm].	4759
Tread depth (mm)	49,5
Number of lugs	21x2
Lug width (mm)	40
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
149 D	3250	65		2,40	