

## TYRES

Product group	Tyres
Item number	72400335
Valid tyre size	335 / 80 R 20
LI / SI / PR	150 K
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 33
Sonderpostenkategorie	Disassembled
type of damage	Runout



## Notes and features

- The BKT Earthmax SR 33 is a radial MPT tyre
- The block pattern provides very good traction on soft, sandy or muddy ground
- The wide spaces between the tread pattern blocks enable very good self-cleaning
- The strong, all-steel casing ensures excellent cut resistance and a long service life

## Technical Informations

Item number	72400335
Valid tyre size	335 / 80 R 20
LI / SI / PR	150 K
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 33
M+S	M+S
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	64,65
Recommended rim size	11.00
Maximum air pressure [bar].	6,50
Section width (mm)	335
Outer diameter of tyre [mm].	1047
Stat. radius (SLR) [mm]	464
Rolling circumference [mm].	3145
Tread depth (mm)	16,5
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
150 K	3350	110		6,50	
	4150	30		7,50	
	4500	25		7,60	