

TYRES

Product group	Tyres
Item number	72400340
Valid tyre size	800 / 65 R 32
LI / SI / PR	181 A8 / 178 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 600
Sonderpostenkategorie	Disassembled
type of damage	Dismounted, Flap damage



Notes and features

- The RT 600 is specially designed for grassland use and sensitive soils.
- Ideal for forage harvesters for green forage harvesting.
- Rounded shoulders and reduced tread depth protect the turf.
- Large footprint enables excellent flotation properties.
- Reinforced bead provides high load capacity.

Technical Informations

Item number	72400340
Valid tyre size	800 / 65 R 32
Alternative size 1	30.5LR32
LI / SI / PR	181 A8 / 178 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 600
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	304,00
Recommended rim size	DW27B
Permitted rim size	DH27B, DW25B
Maximum air pressure [bar].	3,60
Section width (mm)	775
Tread width (mm)	714
Outer diameter of tyre [mm].	1820
Stat. radius (SLR) [mm]	823
Speed Radius Index (SRI)	875
Rolling circumference [mm].	5558
Tread depth (mm)	45,0
Number of lugs	26x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
181 A8	8250	40		3,60	
178 B	7500	50		3,60	