

RIMS

Product group	Rims
Item number	72400342
Valid rim size	6 J x 15 H2
Rim connection	5/66.6/112
Offset (mm)	+30
Rim colour	Black
Brand	Diverse
Sonderpostenkategorie	Damaged
type of damage	Optical defect



Technical Informations

Load capacity of rim 1 [kg]	1000
Speed Rims 1 [km/h]	140
Maximum speed [km/h].	140
Type of drive	Towed axle
Nettogewicht [kg] (gültig)	8,50
Hump	H2
Single / multi-part	einteilig
Rim material	aluminium
Cavity Sealed	No
Verschweißung beidseitig	No
Ventilation holes	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Rim centering	BC
Number of bolt holes	5
Bolt hole diameter [mm]	15
Countersinking	Cone
Countersinking of the cone [°].	C60
hub hole diameter [mm].	66.6
Bolt hole circle diameter [mm]	112
Valve seat	External Valve
Preassembled valve	No
TPMS-kompatibles Ventil	No