

TYRES

Product group	Tyres
Item number	72400367
Valid tyre size	600 / 65 R 38
LI / SI / PR	162 A8 / 159 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 657
Sonderpostenkategorie	Disassembled
type of damage	Dismounted,Runout



Notes and features

- The BKT Agrimax RT 657 is a wide tyre of the 65 series in the power range up to 250 hp.
- Due to the solid lugs and the large contact area, the tyre provides excellent traction even when working on the most difficult soils.
- At the same time, its high air volume and variable inflation pressure adjustment ensure optimum soil protection.
- On the road, the tyre guarantees high ride comfort combined with low rolling resistance and thus low fuel consumption.
- For road transport, the tyre is approved for speeds up to 65 km/h.

Technical Informations

Item number	72400367
Valid tyre size	600 / 65 R 38
LI / SI / PR	162 A8 / 159 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 657
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	195,21
Recommended rim size	DW20B
Permitted rim size	W18L
Maximum air pressure [bar].	2,40
Section width (mm)	611
Tread width (mm)	566
Outer diameter of tyre [mm].	1745
Stat. radius (SLR) [mm]	790
Speed Radius Index (SRI)	825
Rolling circumference [mm].	5247
Tread depth (mm)	55,0
Number of lugs	21x2
Lug width (mm)	46-47
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
162 A8	4750	40		2,40	
159 D	4375	65		2,40	