

TYRES

Product group	Tyres
Item number	72400371
Valid tyre size	800 / 70 R 38
LI / SI / PR	181 A8 / 178 D
TL/TT	TL
Brand	ВКТ
Tread pattern	Agrimax Fortis
Sonderpostenkategorie	Damaged
type of damage	Stud damage





Notes and features

- Super wide tyres for high performance tractors from about 200 hn.
- High load capacities paired with excellent traction, due to extended contact area and solid lugs.
- Efficient in agricultural use and increased transport performance with high ride comfort and lower rolling resistance.
- Reduction of operating costs through fuel savings and high mileage.



Technical Informations

Item number	72400371
Valid tyre size	800 / 70 R 38
LI / SI / PR	181 A8 / 178 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Fortis
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	384,44
Recommended rim size	DW25B
Permitted rim size	DW23B, DW27B
Maximum air pressure [bar].	2,40
Section width (mm)	798
Outer diameter of tyre [mm].	2085
Stat. radius (SLR) [mm]	912
Rolling circumference [mm].	6202
Tread depth (mm)	60,0
Number of lugs	21x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
181 A8	8250	40		2,40	
178 D	7500	65		2,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.