Bohnenkamp Moving Professionals

TYRES

Product group	Tyres		
Item number	72400374		
Valid tyre size	710 / 75 R 42		
LI / SI / PR	175 D / 172 E		
TL/TT	TL		
Brand	ВКТ		
Tread pattern	Agrimax Fortis		
Sonderpostenkategorie	Disassambled		
type of damage	Dismounted,Runout,Flap damage		



Notes and features

- Super wide tyres for high performance tractors from about 200 hp.
- High load capacities paired with excellent traction, due to extended contact area and solid lugs.
- Efficient in agricultural use and increased transport performance with high ride comfort and lower rolling resistance.
- Reduction of operating costs through fuel savings and high mileage.

Bohnenkamp Moving Professionals

Technical Informations

Item number	72400374
Valid tyre size	710 / 75 R 42
LI / SI / PR	175 D / 172 E
TL/TT	TL
Brand	ВКТ
Tread pattern	Agrimax Fortis
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	389,21
Recommended rim size	DW23B
Permitted rim size	DW25B
Maximum air pressure [bar].	2,40
Section width (mm)	716
Outer diameter of tyre [mm].	2133
Stat. radius (SLR) [mm]	970
Rolling circumference [mm].	6406
Tread depth (mm)	62,0
Number of lugs	22x2
Lug width (mm)	55
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
175 D	6900	65		2,40	
172 E	6300	70		2,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.