

## TYRES

|                       |                          |
|-----------------------|--------------------------|
| Product group         | Tyres                    |
| Item number           | 72400380                 |
| Valid tyre size       | 600 / 50 R 22.5          |
| LI / SI / PR          | 164 J                    |
| TL/TT                 | TL                       |
| Brand                 | Alliance                 |
| Tread pattern         | 398                      |
| Sonderpostenkategorie | Disassembled             |
| type of damage        | Dismounted,Irregular run |



## Notes and features

- The Alliance 398 is a POR (Professional Off Road) tyre for use on agri-trucks in all weather and soil conditions.
- It is suitable for field applications as well as for road transport at speeds up to 100 km/h.
- In field use, the traction tread pattern provides very good self-cleaning properties, high traction and low soil compaction.
- The all-steel casing with 4 steel belt inserts guarantees excellent stability and a long service life.
- During road transport, the tyre stands out with low temperature development, low vibration and low noise.
- For road use with speeds of 100 km/h, the inflation pressure must be increased according to the manufacturer's inflation table.
- The tyre is also suited to forestry applications and can be used in wood chip production and in the construction and maintenance of forest paths.
- Use with a tyre pressure control system is possible.
- The tyre is very compatible with the Alligator tyre management.

## Technical Informations

|                              |                 |
|------------------------------|-----------------|
| Item number                  | 72400380        |
| Valid tyre size              | 600 / 50 R 22.5 |
| LI / SI / PR                 | 164 J           |
| TL/TT                        | TL              |
| Brand                        | Alliance        |
| Tread pattern                | 398             |
| Carcass properties           | All-Steel,POR   |
| Antistatic                   | No              |
| Tyre colour                  | Black           |
| Nettogewicht [kg] (gültig)   | 148,00          |
| Recommended rim size         | 20.00           |
| Maximum air pressure [bar].  | 6,50            |
| Section width (mm)           | 620             |
| Outer diameter of tyre [mm]. | 1172            |
| Stat. radius (SLR) [mm]      | 541             |
| Rolling circumference [mm].  | 3605            |
| Tread depth (mm)             | 30,0            |
| Number of lugs               | 18x2            |
| E-Ready                      | No              |

## Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 164 J | 5000               | 100          |               | 6,50                     |              |